



Full Line Of Tire Changers

FOR ALL OF TODAY'S VEHICLES... AND TOMORROW'S



626THP Tilt Tower

- Elite pneumatic tilt tower tire changer comes standard with the Accu-Pro Mounting Helper to clamp up to 26" outside.
- Heavy tower and cabinet for maximum rigidity saves wheels from damage by eliminating tower flex.
- The Accu-Pro's 3-point positioning makes mounting low-profile, PAX and run-flat tires effortless.
- High-performance mount/demount head with tire iron slot provides an extra pressure point for added versatility.
- Proven to withstand the high demands of a high volume tire shop.
- Tested and PAX approved. Optional PAX Adapter, part #SM102666.



Adjustable 3-position bead-breaker to accommodate large wheel diameters with a telescopic adjustment to increase width capability.



Unique telescoping tower allows for wide rims and produces added strength.



Optional jaw protector covers, part #SM103394 lock into place for extra safety. Protector covers prevent accidental rim damage.



Non-opposing adjustable jaws with embossed dimensions for easy, fast and accurate clamping.



Safety Inflation System secures rim during inflation to prevent operator injury and decrease shop liability.

526THP Tilt Tower

- High-end tire changer with manual tilt tower provides outside clamping up to 26".
- Heavy tower and cabinet for maximum rigidity saves wheels from damage by eliminating tower flex.
- Non-opposing jaws with embossed dimension makes clamping faster and more accurate.
- Accu-Pro Mounting Helper Assembly assists in mounting and demounting low-profile and run-flat tires.
- High-performance mount/demount head with tire iron slot designed for low profile tires.
- Three-position bead-breaker with telescoping adjustments increase depth and width bead-breaking capacity.
- Inflation jets, built into clamps, ensure correct positioning for easy bead setting.
- PAX capable with optional PAX adapter kit, part #SM102666.



Model 526T is available without the Accu-Pro Mounting Helper System.

Accu-Pro Pneumatic Mounting System (HP)

Integrated rollers and bead depressor designed to apply pressure in the right places to keep the top bead in the drop center, preventing accidental reseating.

Avoid rim damage - no metal contact with rim.



Hands-Free - Mount the most difficult high-performance low-profile tires with ease. Changing low-profile, run-flats and PAX tires only requires one technician.



Accu-Pro Mounting Helper shown easily mounting the top bead on 26" rim.



Locking roller disc lifts and removes bottom bead effortlessly and securely.

Swing Arm Tire Changers

326SFA & 326S

- 26" Outside clamping capacity standard.
- Three-position adjustable bead-breaker accommodates large wheels and tires.
- Designed to provide maximum rigidity and torque.
- High-performance mount/demount head with tire iron slot designed for low-profile tires.
- Features adjustable non-opposing jaws with inflation jets.
- Following Arm (FA) assist applies additional pressure points to easily mount difficult tire.

Model 326S is available without the Following Arm (FA).



320S

- Classic swing arm design for outside clamping capacity up to 21".
- Three position bead-breaker arm to accommodate large wheels and tires.
- High-performance mount/demount head with tire iron slot designed for low profile tires.
- Non-opposing jaws with inflation jets.
- Avoid injury with the standard Safety Restraint Inflation System.

Speciality Tire Changers

220A

- Articulating arm design with 21" outside clamping capability.
- Uniquely designed for independent automotive shops.
- Adjustable bead-breaker to accommodate up to 16" wide tires.
- Plastic mount/demount head for extra wheel protection.
- Optional plastic jaw covers available, part # SM101402.
- Standard Safety Inflation System secures rim during inflation.



High-performance mount/demount head with tire iron slot designed to provide extra assistance and increase versatility.

The optional Bead Depressor Tool, part # SM103261 assists in mounting low-profile tires



Heavy Duty Tire Changers

Accu-turn Heavy-Duty Tire Changers Standard Features:

- Single piece heavy steel frame construction.
- Bi-directional chuck offers two rotation speeds.
- Low-voltage movable remote control for added safety and versatility.
- Hydraulic gearbox with pressure regulating valve.
- Four-jaw universal chuck lifts and operates in vertical position. (Models 452HD and 426HD).

460HD

The ideal tire changer for handling farm wheels, over-the-road wheels, as well as earth moving and industrial wheels ranging from 14" to 60". Features a six-jaw universal chuck for stronger and more secure clamping. Unique telescoping mounting device for extra ease.



426HD

Well-suited to accommodate truck and bus wheels from 14" to 26", including tubeless rim or tire with rings.



452HD

This versatile tire changer is capable of handling a large range of wheels ranging from 14" to 56" including rims with wells, tubeless rims or rims with a ring.



	460HD	452HD	426HD
Inside Clamping	14-60"	14-56"	14-26"
Rim/Tire Width	61"	35"	31.5"
Tire Diameter	114"	90.5"	64.5"
HP Motor	1	1	1
Electric Requirements	220V, 3PH	220V, 3PH	220V, 3PH
Weight	3750	1945	1310
Width	114"	82"	64"
Depth	105"	69"	55"
Height	82"	69"	49"

Specifications and Features

	220A	320S	326S	326SFA	526T	526THP	626THP
Inside Clamping	12-23"	12-23"	12-28"	12-28"	12-28"	12-28"	12-28"
Outside Clamping	10-21"	10-21"	10-26"	10-26"	10-26"	10-26"	10-26"
Rim/Tire Width	12"	12"	12"	12"	15"	15"	16"
Rim Width	13"	15"	15"	15"	15"	15"	15"
Tire Diameter	46"	40"	44"	44"	40"	40"	40"
Bead-Breaker Capacity	16"	16"	18"	18"	18"	18"	18"
Air Pressure	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs	100-170 lbs
HP Motor	1	1	1	1	1	1	1
Electric Requirement	120v 20 A	120v 20 A	120v 20 A	120v 20 A	120v 20 A	120v 20 A	120v 20 A
Weight	451 lbs	500 lbs	500 lbs	550 lbs	500 lbs	750 lbs	900 lbs
Width	30"	30"	30"	30"	30"	30"	30"
Depth	44 ½"	37 ½"	37 ½"	37 ½"	37 ½"	37 ½"	37 ½"
Height	70"	68"	74"	74"	72"	72"	72"
Articulating Arm	X						
Swing Arm		X	X	X			
Tilt Tower					X	X	X
Dual Cylinder Mnt Helper (Accu-Pro)						X	X
Telescoping Tower							X
Telescoping Bead-Breaker	X	X	X	X	X	X	X
3-Position Bead-Breaker		X	X	X	X	X	X
Non-opposing Jaws	X	X	X	X	X	X	X
Adjustable Jaws			X	X	X	X	X
Inflation Jets Move With Jaws		X	X	X	X	X	X
Slotted Mount Head For Low-Profile Tires	X	X	X	X	X	X	X
Safety Restraint Inflation System	X	X	X	X	X	X	X
Powder Coat Finish	X	X	X	X	X	X	X
5-Year Transmission Warranty	X	X	X	X	X	X	X

Speciality Tire Changers



730 PRO

- Only true fluid hydraulic system on the market.
- Utilize the same hydraulic technology found in heavy-duty tire changers and automotive lifts.
- Faster, stronger, and more reliable than air hydraulic systems.
- Extreme versatility - easily change golf cart tires to run-flat, low-profile, and Z-rated tires to 4X4 mud tires.
- Largest range capacity in the market, up to 60".
- Turntable actually moves forward to accommodate a wider range of wheels and tires.
- Quick-nut swiftly secures wheels to center post.
- Simple operation makes technician training quick and easy.
- User-friendly hand and foot controls.
- Convenient storage bins keep tools within technician's reach.
- Plastic mount/demount slotted head for extra wheel protection and versatility.

Specifications

Clamping Capacity	8" - 32"
Rim / Tire Width	16"
Rim Width	16"
Tire Diameter	60"
Air Pressure Req	100 - 170 lbs.
Motor	2HP
Electric Requirement	220 v
Weight	1200 lbs
Width	30"
Depth	55"
Height	78"



Dual clamping rollers make tire to rim matching fast and effortless.



Three-point bead depression system easily mounts difficult top tire beads.



Integrated wheel lift with rollers provides extra assistance to technician.




SM102666
PAX Tire Kit for use with Accu-Pro Mounting Helper (includes roller, rim protectors, bead levers, and center post adaptors).



SM101402
Plastic clamping jaw protectors for models 220A and 320S. Use **SM103394** for models 326S/SFA, 526T/THP, and 626THP.



SM103261
Zeppa bead depressor tool for standard drop center rims. Use **SM103216** Zeppa bead depressor tool for deep drop center rims (more than 2").



SM102014
Set of four 8" wheel clamp adaptors for 8" wheels on models 220A and 320S. Use **SM103286** for models 326S/SFA, 526T/THP, and 626THP.



SM102529
Plastic duck head kit (requires 102765 adaptor for all models except 220A).




SM102090
Bead breaker plastic protection kit (includes SM101800 and SM102088).



SM102725
Plastic protection for back side of mount/demount heads.



SM102724
Set of four motorcycle clamp adaptors for use on models 220A and 320S. Use **SM103284** for models 326S/SFA, 526T/THP, and 626THP.



SM103076
Set of four 26" turntable clamp adaptors for models 220A and 320S.



SM102711
Inflation system kit.



SM101608
Mount/demount head protective plastic inserts (pack of 5).



SM103302
Bead depressor tool, adjustable plastic clamp style.

Accu Offers a Complete Line of Wheel Service Equipment



LOCALLY DISTRIBUTED BY



Accu Industries, Inc.

Headquarters:
P.O. Box 15540
Richmond, VA 23227
11126 Air Park Road
Ashland, VA 23005
804-798-8922
Fax 804-798-6742
www.accu-turn.com

Export Department:
Hockman-Lewis Limited
200 Executive Dr.
West Orange, NJ 07052
973-325-3838
Fax 973-325-7974
www.hl-ltd.com